


Absolute maximum ratings





(Ta=25°C)

Symbol	Ratings		Unit
	NPN	PNP	
V _{CBO}	100	−100	V
V _{CEO}	100	−100	V
V _{EBO}	6	−6	V
I _C	5	−5	A
I _{CP}	8 (PW≤1ms, Du≤50%)	−8 (PW≤1ms, Du≤50%)	A
I _B	0.5	−0.5	A
P _T	5 (T _a =25°C)		W
	25 (T _c =25°C)		
V _{ISO}	1000 (Between fin and lead pin, AC)		V _{rms}
T _j	150		°C
T _{stg}	−40 to +150		°C
θ _{J-c}	5		°C/W

Equivalent circuit diagram



Characteristic curves








Electrical characteristics


(Ta=25°C)

Symbol	NPN					PNP				
	Specification			Unit	Conditions	Specification			Unit	Conditions
	min	typ	max			min	typ	max		
ICBO			10	μA	$V_{CB}=100\text{V}$			-10	μA	$V_{CB}=-100\text{V}$
IEBO			10	mA	$V_{EB}=6\text{V}$			-10	mA	$V_{EB}=-6\text{V}$
V_{CEO}	100			V	$I_C=10\text{mA}$	-100			V	$I_C=-10\text{mA}$
h_{FE}	2000				$V_{CE}=4\text{V}, I_C=3\text{A}$	2000				$V_{CE}=-4\text{V}, I_C=-3\text{A}$
$V_{CE(sat)}$			1.5	V	$I_C=3\text{A}, I_B=6\text{mA}$			-1.5	V	$I_C=-3\text{A}, I_B=-6\text{mA}$

Characteristic curves

 $V_{CE(sat)}$ - I_B Characteristics (Typical) θ_{JA} -PW Characteristics $V_{CE(sat)}$ - I_C Temperature Characteristics (Typical)

Pr-Ta Characteristics



Safe Operating Area (SOA)

