

### Features and Benefits

- 3.5V to 24V Operation
- -40°C to 150°C Superior temperature operation
- CMOS technology
- Low current consumption
- Chopper-stabilized amplifier stage
- Open drain output
- Low sensitivity
- Small Size-SOT23 3L and TO-92 3L
- both RoHS compliant packages

### Application Examples

- Automotive, Consumer and Industrial
- Solid-state switch
- Brushless DC motor commutation
- Speed detection
- Angular position detection
- Proximity detection
- Current detector




3 pin SOT23 (suffix LH)



3 pin SIP (suffix UA)

### Functional Block Diagram



UA Package

Pin 1 – V<sub>DD</sub>

Pin 2 – GND

Pin 3 – OUT

SO Package

Pin 1 – V<sub>DD</sub>

Pin 2 – OUT

Pin 3 – GND

### General Descriptions

The S1102 is a unipolar Hall-effect sensor IC fabricated from CMOS technology. The device integrates a voltage regulator, Hall sensor with dynamic offset cancellation system, small signal amplifier, Schmitt trigger and an open-drain output driver. With suitable output pull up, they can be used with bipolar or CMOS logic circuits.

These Hall-effect switches are monolithic integrated circuits with tighter magnetic specifications, designed to operate continuously over extended temperatures to +150°C, and are

more stable with both temperature and supply voltage changes. The unipolar switching characteristic makes these devices ideal for use with a simple bar or rod magnet.

Thanks to its wide operating voltage range and extended choice of temperature range, it is quite suitable for use in automotive, industrial and consumer applications.



The device is delivered in a Small Outline Transistor (SOT) and in a Plastic Single In Line (TO-92 flat). Both 3-lead packages are RoHS compliant.

### Glossary of Terms

MilliTesla (mT),	Gauss Units of magnetic flux density: 1mT = 10 Gauss
RoHS	Restriction of Hazardous Substances
Operating Point ( $B_{OP}$ )	Magnetic flux density applied on the branded side of the package which turns the output driver ON ( $V_{OUT} = V_{DSon}$ )
Release Point ( $B_{RP}$ )	Magnetic flux density applied on the branded side of the package which turns the output driver OFF ( $V_{OUT} = \text{high}$ )

**Pin Definitions and Descriptions**

SOT Pin №	SIP Pin №	Name	Type	Function
1	1	VDD	Supply	Supply Voltage pin
2	3	OUT	Output	Open Drain Output pin
3	2	GND	Ground	Ground pin


**Absolute Maximum Ratings**

Parameter	Symbol	Value	Units
Supply Voltage	VDD	28	V
Supply Current	IDD	50	mA
Output Voltage	VOUT	28	V
Output Current	IOUT	50	mA
Storage Temperature Range	TS	-65 to 170	°C

Absolute maximum ratings

Operating Temperature Range	Symbo	Value	Units
Temperature Suffix "E"	TA	-40 to 85	°C
Temperature Suffix "L"	TA	-40 to 150	°C

Exceeding the absolute maximum ratings may cause permanent damage. Exposure to absolute-maximum- rated conditions for extended periods may affect device reliability.

## General Electrical Specifications

DC Operating Parameters  $T_A = 25^\circ\text{C}$ ,  $V_{DD} = 3.5\text{V to } 24\text{V}$  (unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Units
Supply Voltage	VDD	Operating	3.5		24	V
Supply Current	IDD	$B < B_{RP}$	1.5	2.5	5	mA
Output Saturation Voltage	VDSon	$I_{OUT} = 20\text{mA}$ , $B > B_{OP}$		0.4	0.5	V
Output Leakage Current	IOFF	$B < B_{RP}$ $V_{OUT} = 24\text{V}$		0.01	10	$\mu\text{A}$
Output Rise Time	tr	$R_L = 1\text{k}\Omega$ , $C_L = 20\text{pF}$		0.25		$\mu\text{s}$
Output Fall Time	tf	$R_L = 1\text{k}\Omega$ , $C_L = 20\text{pF}$		0.25		$\mu\text{s}$

## Magnetic Specifications


DC Operating Parameters  $V_{DD} = 3.5\text{V to } 24\text{V}$  (unless otherwise specified)

S1102


Parameter	Symbol	Test Conditions	Min	Typ	Max	Units
Operating Point	$B_{OP}$	$T_A = 25^\circ\text{C}$ , $V_{DD} = 12\text{V DC}$	100		150	G
Release Point	$B_{RP}$		60		130	G
Hysteresis	$B_{HYS}$			30		G

## Application Information

### Typical Three-Wire Application Circuit



### Automotive and Harsh, Noisy Environments Three-Wire Circuit



### Application Comments

For proper operation, a 100nF bypass capacitor should be placed as close as possible to the device between the VDD and ground pin. For reverse voltage protection, it is recommended to connect a resistor or a diode in series with the VDD pin.

When using a resistor, three points are important:

- the resistor has to limit the reverse current to 50mA maximum ( $VCC / R1 \leq 50mA$ )
- the resulting device supply voltage VDD has to be higher than VDD min ( $VDD = VCC - R1 \cdot I_{DD}$ )
- the resistor has to withstand the power dissipated in reverse voltage condition ( $PD = VCC^2 / R1$ )

When using a diode, a reverse current cannot flow and the voltage drop is almost constant ( $\approx 0.7V$ ).

Therefore, a 100  $\Omega$ /0.25W resistor for 5V application and a diode for higher supply voltage are recommended.

Both solutions provide the required reverse voltage protection.

When a weak power supply is used or when the device is intended to be used in noisy environment, it is recommended that figure 13.3 from the Application Information section is used.

The low-pass filter formed by R1 and C1 and the zener diode Z1 bypass the disturbances or voltage spikes occurring on the device supply voltage VDD. The diode D1 provides additional reverse voltage protection.


### ESD Precautions

Electronic semiconductor products are sensitive to Electro Static Discharge (ESD).


Always observe Electro Static Discharge control procedures whenever handling semiconductor products.

### Package Information

Package UA, 3-Pin SIP(TO-92):



### Package LH, 3-Pin (SOT-23)




#### Notes:

- PINOUT: Pin 1 VDD  
Pin 2 Output  
Pin 3 GND
- All dimensions are in millimeters ;

#### Marking:

58 -- Code of Device (58 or 44);  
XXX -- Production Lot ;

#### End View



### Ordering Information

Part No.	Pb-free	Temperature Code	Package Code	Packing
S1102	YES	E (-40°C to 85°C)	LHLT(SOT-23)	7-in. reel, 3000 pieces/reel
S1102	YES	E (-40°C to 85°C)	UA(TO-92)	Bulk, 1000 pieces/bag
S1102	YES	L (-40°C to 150°C)	LHLT(SOT-23)	7-in. reel, 3000 pieces/reel
S1102	YES	L (-40°C to 150°C)	UA(TO-92)	Bulk, 1000 pieces/bag